## **ULTRASONIC PROBE**

Patent number:

JP11347032

**Publication date:** 

1999-12-21

Inventor:

TAKEDA JUNICHI; IRIOKA KAZUYOSHI; TOKUNAGA WATARU

Applicant:

MATSUSHITA ELECTRIC IND CO LTD

Classification:

- international:

A61B8/00; G01N29/24; H04R17/00


- european:

Application number: JP19980170527 19980604 Priority number(s): JP19980170527 19980604

Report a data error here

## Abstract of JP11347032

PROBLEM TO BE SOLVED: To increase operability, bearing resolving power in a short distance, and penetration in a long distance of the ultrasonic probe by narrowing a piezoelectric plate in the minor axis direction. SOLUTION: The takeout port of a ground electrode 2, which is formed at the ultrasonic wave radiation side of a piezoelectric plate 1 of this ultrasonic probe, is disposed at an exposed part 7 of the end side in the scanning direction, and the take- out port is connected to the outside using a common ground line 11. As the effective opening width in the minor axis direction is the same as the width of the piezoelectric plate 1 in the monitor axis direction, the width of the ultrasonic probe can be reduced in the minor axis direction, resulting in improved operability. As, with the same width of a piezoelectric oscillator, the effective opening width in the minor axis direction of ultrasonic wave radiated from the piezoelectric plate 1 becomes larger, even when used for scanning from narrow gaps such as intercostal scanning, a good ultrasonic tomograph is obtained in which reflection noise signal is reduced from the rib. The ground electrode 2 of the piezoelectric oscillator is divided in the minor axis direction and they are selected by a switch, so the effective opening width in the minor axis direction can be varied to form a suitable beam corresponding to an area to be measured, resulting in improving the bearing resolving power in a short distance as well as the penetration in a long distance.



Data supplied from the esp@cenet database - Worldwide